



ATTO Technology, Inc. 10 GbE to Thunderbolt™ adapters provide maximum throughput for high bandwidth network connectivity for demanding IT and media & entertainment applications.

TECHNICAL FEATURES

- Dual 10GbE (SFP+ LC Optical) ports
- Supports 4K video file transfer and display simultaneously with dual 20Gb/s Thunderbolt 2
- Supports ATTO Xtend SAN™ iSCSI initiator
- Daisy chain up to five additional Thunderbolt technology enabled devices
- Backwards compatible with 10Gb/s Thunderbolt
- Exclusive Advanced Data Streaming (ADS™) Technology
- Minimized interrupts for low latency
- TCP, UDP and IPv4 checksum offloading and Tx/TCP segmentation offloading
- Industry's lowest power consumption
- Three-year standard product warranty
- RoHS Compliant

ATTO ThunderLink® NS 2102

THUNDERBOLT™ 2 TO 10GbE SFP+ OPTICAL

INDUSTRY PROVEN TECHNOLOGY

ATTO Technology, Inc. has nearly 30 years of experience developing first-to-market high performance and reliable storage connectivity solutions for customers. ATTO ThunderLink® Ethernet adapters now provide creative professionals using Thunderbolt™ enabled hosts, cost effective access to storage not previously available using FireWire or USB. The integrated family of ThunderLink adapters boasts an extensive list of customer design wins and certifications with respected industry partners.

FLEXIBLE CONNECTIVITY SOLUTIONS

ATTO 10GbE adapters provide the most flexible and scalable connectivity for today's high bandwidth content creation environments. By leveraging support for software iSCSI initiators, including ATTO Xtend SAN™, ThunderLink 10GbE adapters can support both local and storage area networks. ThunderLink 10GbE adapters offer driver support for macOS® and Windows®, providing a single connectivity solution for customers with heterogeneous operating system environments.

PERFORMANCE ENGINEERED

With 10Gb data transfer rates and multiple offloads (TCP, IPv4, UDP), ATTO Ethernet Thunderbolt adapters are the premier connectivity choice for bandwidth-intensive applications such as data back-up and restoration, IP content delivery, medical imaging and video rendering. With multi-core processors driving the need for higher bandwidth, ThunderLink 10GbE delivers superior throughput to meet that need.

ADVANCED MANAGEMENT TOOLS

ThunderLink 10GbE adapters provide a common foundation for both local and storage networks. The ThunderLink NS 2102 leverages standard OS management and monitoring tools to dramatically reduce the cost and complexity of a data center's administration and infrastructure.

ATTO ThunderLink® NS 2102

THUNDERBOLT™ 2 TO 10GbE SFP+ OPTICAL

APPLICATIONS

ThunderLink® 10GbE adapter solutions combine the unparalleled performance of 10Gb Ethernet, the lossless benefits of Enhanced Ethernet and robustness of iSCSI initiator software, to meet the performance and economic needs of today's growing data centers. The ThunderLink NS 2102 is ideal for applications that require low latency, high bandwidth data transfers, such as data back-up and restoration, video-on-demand and video streaming, medical imaging, and clustered databases.

GENERAL FEATURES

- Data rate per port: 10GbE
- TCP, UDP, IPv4, and IPv6 checksum offloading
- Tx/TCP segmentation offload (Large Send Offload—LSO)
- Low latency interrupts
- Interrupt Coalescing/Moderation
- Interrupt levels INTA, MSI, MSI-X
- Data Center Bridging (DCB) support
- Priority-Based Flow Control 802.1Qbb rev.0
- Enhanced Transmission Selection 802.1Qaz rev.0 protocol
- Header splits and Replication in Receive
- Receive Side Scaling for multiple Rx queues
- Direct Cache Access (DCA) eliminates cache misses and reduces CPU load
- IEEE 802.3 2005 flow control support
- 802.1p—Priority Encoding
- 802.1q—VLAN Tagging
- 802.3ad—Link Aggregation
- Override MAC Address
- VLAN support with tag insertion and stripping
- Plug and play specification support
- Advanced Packet Filtering

ADVANCED SOFTWARE FEATURES

- Adaptive load balancing
- Teaming support
- PCI Hot Plug/Active peripheral interconnect

MANAGEMENT TOOLS

- Easy system monitoring with Simple Network Management Protocol (SNMP) and Remote Network Monitoring (RMON) Statistic Counters
- Watchdog Timer for chip/driver status monitoring

EXTERNAL CONNECTIVITY

- 10Gb/s, 1Gb/s, 100Mb/s SFP+ LC fiber-optic connectors (short wave)
- Two LED indicators per port
- LED Indicators: LINK (solid), ACTIVITY (blinking), LINK SPEED (ON = 10Gb, OFF = 1Gb)

NETWORK STANDARDS

- IEEE802.3ae: 10GBASE-SR, 10GBASE-LR
- SFF-8431: 10GSFP+Cu (Direct Attach Copper)
- 802.1 qbb: Priority Flow Control

OPERATING SYSTEM SUPPORT

- macOS®
- Windows®

POWER ADAPTER

- 100-240VAC, 50-60Hz, 0.6A Max
- 12VDC

COMPLIANCE

- FCC Part 15 Subpart B, Class B
- EN55032, Class B/EN55024
- EN60950-1
- EN60825-1
- EN60825-2
- cTUVus
- EU RoHS (2011/65/EU)
- TAA Compliant (Country of Origin: USA)

OPERATING TEMPERATURE

HARDWARE ENVIRONMENT

- Temperature: 0-40° C
- Humidity: 10 - 90% non-condensing

STORAGE ENVIRONMENT

- Temperature: -40° C to 70° C
- Humidity: 5- 95% non-condensing

DIMENSIONS

- 8.66"(D) x 4.07"(W) x 1.20"(H)

WARRANTY

- Three Years

ORDERING INFORMATION

- Phone: 716-691-1999
- Thunderbolt 2 to 10GbE SFP+ LC
- ThunderLink NS 2102: TLNS-2102-D01
- ThunderLink NS 2102: TLNS-2102-DE1

COMPLEMENTARY PRODUCTS

- ATTO Celerity™ Fibre Channel HBAs
- ATTO ExpressSAS® HBAs and RAID adapters
- ATTO FastFrame™ NICs
- ATTO FibreBridge® Fibre Channel bridges
- ATTO premium cables



ThunderLink®	NS 2102
Model Number	TLNS-2102-D01 TLNS-2102-DE1
Input Connectors	(2) 20Gb/s Thunderbolt™
Output Connectors	(2) 10GbE
Connector Type	SFP+ LC Optical
Form Factor	Desktop
Warranty	3 Year